




















	Standard	Result
 <b>Size</b>		1500,0 X 250,0
 <b>Thickness</b>		4,5 mm
 <b>Wear layer</b>		0,55 mm
<b>Surface treatment</b>		K-Guard+ PU coating
<b>Guarantee</b>	Light industrial	10 years
	Commercial	12 years
	Domestic	30 years
 <b>Bevelled edge</b>		No
 <b>Standards</b>	EN 649	Heterogeneous PVC
 <b>Classification</b>	EN 685- Light industrial	42: Light industrial general
	EN 685- Commercial	33: Commercial heavy
	EN 685- Domestic	23: Domestic heavy
 <b>Reaction to fire</b>	EN 13501-1	B <sub>f1</sub> -s1
	EN ISO 9239-1	Pass
	EN ISO 11925-2	Pass
 <b>Staining resistance</b>	EN 423	Class 0
 <b>Light fastness</b>	EN ISO 105-B02	≥7
 <b>Abrasion resistance</b>	EN 660-2	Group T
 <b>Dimensional stability</b>	EN 434	≤ 0,10%
 <b>Acoustic Impact noise reduction</b>	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 13 dB
 <b>Electrical behaviour body voltage</b>	EN 1815	Pass
 <b>Indentation - residual</b>	EN 433	≤ 0,1 mm
 <b>Castor chair continuous use</b>	EN 425	Pass
 <b>Mass per unit area</b>	EN 430	7082 g/m <sup>2</sup>
<b>Thermal conductivity</b>	ISO 8302	0,0245 m <sup>2</sup> K/W
		Suitable for underfloor heating. Max 27°C
<b>**Slip resistance</b>	DIN 51130	R10
	DIN 51097	B
	EN 13893	DS
 <b>Adhesive</b>		Most applications will not require the use of adhesives. However, we recommend the use of a tackifier for heavy traffic areas.
 <b>Recycling</b>		Suitable
 <b>VOC emission</b>	French VOC regulation (ISO 16000)	A+

\*\*Slip resistance is measured on ex-factory product. Slip resistance in use will depend on how the product is maintained

For more information:

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132

Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386

e: [info@designflooring.com](mailto:info@designflooring.com)

[www.designflooring.com](http://www.designflooring.com)

