



# Technical Data

			Slip Resistance			
	Standard	Result	Product	Size (mm)	DIN 51130	DIN 51097
		See separate table	CP4501	1220,0 x 179,0	R10	B
		4,5 mm	CP4503	1220,0 x 179,0	R10	B
		0,4 mm	CP4504	1220,0 x 179,0	R10	B
		Kguard+ PU coating	CP4506	1220,0 x 179,0	R10	B
<b>Guarantee</b>	Light industrial	12 years	CP4507	1220,0 x 179,0	R10	B
	Commercial	12 years	CP4508	1220,0 x 179,0	R10	B
	Domestic	30 years	CP4509	1220,0 x 179,0	R10	B
		No	CP4510	1220,0 x 179,0	R10	B
	EN 649	Heterogeneous PVC	CT4301	600,0 X 307,0	R10	C
	EN 685- Light industrial	41: Light industrial moderate	CT4302	600,0 X 307,0	R10	C
	EN 685- Commercial	32: Commercial general	CT4303	600,0 X 307,0	R10	C
	EN 685- Domestic	23: Domestic heavy	CT4304	600,0 X 307,0	R10	C
	EN 13501-1	B <sub>fl</sub> -s1				
	EN ISO 9239-1	Pass				
	EN ISO 11925-2	Pass				
	EN 423	Class 0				
	EN ISO 105-B02	≥7				
	EN 660-2	Group T				
	EN 434	≤ 0.15%				
	EN ISO 717-2 / EN ISO 140-8	ΔL <sub>w</sub> = 4 db				
	EN 1815	Pass				
	EN 433	≤ 0.1mm				
	EN 425	Pass				
	EN430	8,454 g/m <sup>2</sup>				
	ISO 8302	0,0197 m <sup>2</sup> K/W Suitable for underfloor heating. Max 27°C				
	DIN 51130	See separate table				
	DIN 51097	See separate table				
	EN 13893	DS				
	NF EN ISO 1600	A+ (<250µg/m <sup>2</sup> )				
	DIBt/AgBB	Pass				
	None required; please install according to our installation instructions.					
	Suitable					



For more information:  
T: +44 (0)1386 820105  
F: +44 (0)1386 820132  
info@designflooring.com