

	Standard	Result	Product	Size (mm)
		See separate table	RCT6301	307 x 600
	ISO 24346	6,5 mm	RCT6302	307 x 600
	ISO 24340	0,55 mm	RCT6303	307 x 600
		PU coating	RCT6304	307 x 600
	Commercial	12 years	RCP6501	1220 x 179
	Domestic	30 years	RCP6503	1220 x 179
		No	RCP6504	1220 x 179
	ISO 23997	8.046 g/m ²	RCP6506	1220 x 179
	EN 16511	Multilayer modular floorcovering panels	RCP6507	1220 x 179
			RCP6508	1220 x 179
	ISO 10874 Commercial	33:-commercial heavy	RCP6509	1220 x 179
	ISO 10874 domestic	23:-Domestic heavy	RCP6510	1220 x 179
	EN13501-1	B _{fl} -s1		
	EN 438-2	pass		
	EN ISO 105-B02	pass ≥6		
	EN13329 Annex E	pass 4000 cycles		
	EN424	pass (no visible damage)		
	EN ISO 23999	pass ≤0,25%		
	ISO 24336	pass (0,2 %)		
	EN ISO 10140-3	ΔL _w = 19 dB		
	EN ISO 10140-3	ΔL _{LIN} = 11 dB		
	ISO 24343-1	≤0,1 mm		
	EN13329 Annex F	pass ≥1800 mm		
	ISO 4918	pass 25 000 cycles		
	ISO 8302	0,052 m ² K/W		
		suitable for underfloor heating max 27 °C		
	EN 13893	DS		
	DIN 51130	R10		
	French VOC regulation (ISO 16000)	A+		
		None required; please install according to our installation instructions.		
		Suitable		
		Yes		

*slip resistance is measured on ex-factory product. Slip resistance in use will be affected by surface contamination and by how the product is maintained

For more information:

Designflooring - T: +44 (0)1386 820105 | F: +44 (0)1386 820132

Designflooring SAS - T: 01 57 32 39 13 | F: 01 57 32 39 14

Designflooring GmbH - T: 0211 469 59203 | F: 0211 469 59204

Designflooring Nederland - T: 020 200 8282 | F: 020 200 8386

e: info@designflooring.com



Manufactured to ISO9001



Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+